



MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

Description

The MPC-301X-4L, MPC-302X-4L and MPC-305X-4L series combine an AlGaAs infrared emitting diode as the emitter which is optically coupled to a monolithic silicon random-phase photo triac in a plastic DIP4 package with different lead forming options.

With the robust coplanar double mold structure, MPC-301X-4L, MPC-302X-4L and MPC-305X-4L series provide the most stable isolation feature.


Features

- High isolation 5000 VRMS
- DC input with random-phase photo triac output
- Operating temperature range - 40 °C to 100 °C
- REACH compliance
- Halogen free
- MSL class 1
- Regulatory Approvals
 - UL - UL1577
 - VDE - EN60747-5-5(VDE0884-5)
 - CQC – GB4943.1, GB8898

Applications

- Solenoid/valve controls
- Lighting controls
- Motor controls
- Temperature controls
- Static AC power switches
- Solid state relays
- Interfacing microprocessors to 115 to 240VAC peripherals


SCHEMATIC



PIN DEFINITION

1. Anode
2. Cathode
3. Terminal
4. Terminal

PACKAGE OUTLINE





MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

ABSOLUTE MAXIMUM RATINGS

PARAMETER		SYMBOL	VALUE	UNIT	NOTE
INPUT					
Forward Current		I_F	60	mA	
Reverse Voltage		V_R	6	V	
Junction Temperature		T_j	125	°C	
Input Power Dissipation		P_i	100	mW	
OUTPUT					
Off-state Output Terminal Voltage	MPC-301X-4L	V_{DRM}	250	V	
	MPC-302X-4L		400		
	MPC-305X-4L		600		
Peak Repetitive Surge Current PW=100μs, 120pps		I_{TSM}	1	A	
Junction Temperature		T_j	125	°C	
Output Power Dissipation		P_o	300	mW	
COMMON					
Total Power Dissipation		P_{tot}	400	mW	
Isolation Voltage		V_{iso}	5000	V _{rms}	1
Operating Temperature		T_{opr}	-40~100	°C	
Storage Temperature		T_{stg}	-55~125	°C	
Soldering Temperature		T_{sol}	260	°C	2

Note 1. AC For 1 Minute, R.H. = 40 ~ 60%

Note 2. For 10 seconds



MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

ELECTRICAL OPTICAL CHARACTERISTICS at Ta=25°C							
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION	NOTE
INPUT							
Forward Voltage	V_F	-	1.24	1.4	V	$I_F=10\text{mA}$	
Reverse Current	I_R	-	-	10	μA	$V_R=6\text{V}$	
Input Capacitance	C_{in}	-	8.5	250	pF	$V=0, f=1\text{kHz}$	
OUTPUT							
Peak Off-state Current, Either Direction	I_{DRM}	-	-	100	nA	$V_{DRM}=\text{Rated } V_{DRM}$ $I_F=0$	3
Peak On-state Current, Either Direction	V_{TM}	-	1.58	2.5	V	$I_{TM}=100\text{mA}$ $I_F=\text{Rated } I_{FT}$	
Critical Rate of Rise of Off-state Voltage	dV/dt	1000	-	-	V/ μs	$V_{PEAK}=\text{Rated } V_{DRM}$	4
TRANSFER CHARACTERISTICS							
LED Trigger Current	MPC-3010-4L, MPC-3021-4L, MPC-3051-4L	I_{FT}	-	-	15	mA	Terminal Voltage = 3V $I_{TM}=100\text{mA}$
	MPC-3011-4L, MPC-3022-4L, MPC-3052-4L		-	-	10		
	MPC-3012-4L, MPC-3023-4L, MPC-3053-4L		-	-	5		
Holding Current	I_H	-	257	-	μA		
Isolation Resistance	R_{iso}	10^{12}	10^{14}	-	Ω	DC500V, 40 ~ 60% R.H.	
Floating Capacitance	C_{IO}	-	0.4	1	pF	$V=0, f=1\text{MHz}$	

Note3. Test voltage must be applied within dV/dt rating.

Note4. Refer to Fig.15 & Fig.16



MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

CHARACTERISTIC CURVES

Fig.1 Forward Current vs. Ambient Temperature




Fig.2 On-state Terminal Current vs. Ambient Temperature




Fig.3 Forward Current vs. Forward Voltage




Fig.4 Off-state Terminal Current vs. Ambient Temperature




Fig.5 Normalized Off-state Terminal Voltage vs. Ambient Temperature





Fig.6 Normalized Trigger Current vs. LED Trigger Pulse Width





MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

CHARACTERISTIC CURVES

Fig.7 Normalized Trigger Current vs. Ambient Temperature




Fig.8 On-state Terminal Voltage vs. Ambient Temperature




Fig.9 On-state Terminal Voltage vs. On-state Terminal Current




Fig.10 Holding Current vs. Ambient Temperature




Fig.11 Turn On Time vs. Forward Current





Fig.12 Turn On Time vs. Ambient Temperature





MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

TEST CIRCUITS

Fig.13 Test Circuits of Turn On Time




Fig.14 Waveforms of Turn On Time




Fig.15 Test Circuits of dV/dt





Fig.16 Waveforms of dV/dt







MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series **DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler**

PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)

Standard DIP – Through Hole (DIP Type)



Gullwing (400mil) Lead Forming – Through Hole (M Type)






MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series


DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)

Surface Mount Lead Forming (S Type)



Surface Mount (Low Profile) Lead Forming (SL Type)






MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler


PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)

Surface Mount (Gullwing) Lead Forming (SLM Type)




RECOMMENDED SOLDER MASK (Dimensions in mm unless otherwise stated)

Surface Mount Lead Forming & Surface Mount (Low Profile) Lead Forming



Surface Mount (Gullwing) Lead Forming








MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series




DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

TUBE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Standard DIP



Option M





MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

BOX SPECIFICATIONS (Tube Type)


Inner Box

Label



- L x W x H = 52.5cm x 10.7cm x 4.7cm

Outer Box



- L x W x H = 53.5cm x 23.5cm x 25.5cm

Label






MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series


DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option S(T1) & SL(T1)



Option S(T2) & SL(T2)






MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series


DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option S(T3) & SL(T3)



Option S(T4) & SL(T4)






MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series


DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option SLM(T1)



Option SLM(T2)







MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series
DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

REEL SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option S & Option SL



Option SLM






MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler


BOX SPECIFICATIONS (Reel Type)

Inner Box




- L x W x H = 36cm x 36cm x 6.9cm

Outer Box



- L x W x H = 45cm x 38cm x 38cm





MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

ORDERING AND MARKING INFORMATION

MARKING INFORMATION



MPC : Company Abbr.
30XX : Part Number & Rank
V : VDE Option
Y : Fiscal Year
A : Manufacturing Code
WW : Work Week

ORDERING INFORMATION

MPC-30XX-4L(Y)(Z)-GV

MPC – Company Abbr.
 30XX – Part Number
 (10/11/12/21/22/23/51/52/53)
 -4L – DIP4 Package
 Y – Lead Form Option (M/S/SL/SLM/None)
 Z – Tape and Reel Option (T1/T2/T3/T4)
 G – Green
 V – VDE Option (V or None)

LABEL INFORMATION

Part No : XXXXXXXXXXXXX Bin Code : X

 Lot No : XXXXXXXXXXXX
 Date Code : XXXX
 Q'ty : XXXX pcs




Packing Quantity

Option	Quantity	Quantity – Inner box	Quantity – Outer box
None	100 Units/Tube	32 Tubes/Inner box	10 Inner box/Outer box = 32k Units
M	100 Units/Tube	32 Tubes/Inner box	10 Inner box/Outer box = 32k Units
S(T1)	1500 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 22.5k Units
S(T2)	1500 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 22.5k Units
S(T3)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units
S(T4)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units
SL(T1)	1500 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 22.5k Units
SL(T2)	1500 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 22.5k Units
SL(T3)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units
SL(T4)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units
SLM(T1)	1500 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 22.5k Units
SLM(T2)	1500 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 22.5k Units




MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

REFLOW INFORMATION

REFLOW PROFILE



Profile Feature	Sn-Pb Assembly Profile	Pb-Free Assembly Profile
Temperature Min. (T _{smin})	100°C	150°C
Temperature Max. (T _{smax})	150°C	200°C
Time (t _s) from (T _{smin} to T _{smax})	60-120 seconds	60-120 seconds
Ramp-up Rate (t _L to t _P)	3°C/second max.	3°C/second max.
Liquidous Temperature (T _L)	183°C	217°C
Time (t _L) Maintained Above (T _L)	60 – 150 seconds	60 – 150 seconds
Peak Body Package Temperature	235°C +0°C / -5°C	260°C +0°C / -5°C
Time (t _P) within 5°C of 260°C	20 seconds	30 seconds
Ramp-down Rate (T _P to T _L)	6°C/second max	6°C/second max
Time 25°C to Peak Temperature	6 minutes max.	8 minutes max.




MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

TEMPERATURE PROFILE OF SOLDERING

WAVE SOLDERING (JESD22-A111 COMPLIANT)



HAND SOLDERING BY SOLDERING IRON

Soldering Temperature	380+0/-5°C
Soldering Time	3 sec max.

- One time soldering is recommended for all soldering method.
- Do not solder more than three times for IR reflow soldering.



MPC-301X-4L, MPC-302X-4L, MPC-305X-4L Series

DIP4, DC Input, Random-Phase Photo TRIAC Optocoupler

- MEMCHIP is continually improving the quality, reliability, function and design. MEMCHIP reserves the right to make changes without further notices.
- The characteristic curves shown in this datasheet are representing typical performance which are not guaranteed.
- MEMCHIP makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, MEMCHIP disclaims (a) any and all liability arising out of the application or use of any product, (b) any and all liability, including without limitation special, consequential or incidental damages, and (c) any and all implied warranties, including warranties of fitness for particular
- The products shown in this publication are designed for the general use in electronic applications such as office automation, equipment, communications devices, audio/visual equipment, electrical application and instrumentation purpose, non-infringement and merchantability.
- This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or lifesaving applications or any other application which can result in human injury or death.
- Please contact MEMCHIP sales agent for special application request.
- Immerge unit's body in solder paste is not recommended.
- Parameters provided in datasheets may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated in each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify MEMCHIP's terms and conditions of purchase, including but not limited to the warranty expressed therein.
- Discoloration might be occurred on the package surface after soldering, reflow or long-time use. It neither impacts the performance nor reliability.